

MARINEGEN ISO 7840 A1 L/L

FUEL DELIVERY HOSE FOR ON LEISURE BOATS - LONG LENGTH



APPLICATION

Delivery hose for diesel, bio diesel fuel and for eco gasoline, for marine engines installed on leisure boats (up to 24m)

TUBE

Black, smooth, **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, **CR** rubber compound, self extinguishing, resistant to heat, fuels, and weathering

WORKING TEMPERATURE

-4°F + 212°F

SPECIFICATIONS

ISO 7840:2004 A1 CE LL, approved RINA SAE J 1527:2004 A1

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
6	1/4	16	5/8	0,26	3,4	50	14	200	30/100
8	5/16	17	21/32	0,28	3,4	50	14	200	30/100
10	3/8	20	25/32	0,37	3,4	50	14	200	30/100
12	1/2	22	7/8	0,47	2,5	40	10	150	30/100
16	5/8	27	1 3/16	0,55	2,5	40	10	150	30/100
19	3/4	30	1 7/32	0,65	2,5	40	10	150	30/100

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT MARINEGEN ISO 7840:2004 A1 CE L/L RINA DIP SAE J 1527.2004 A1 ITALY