

## WELBLU 20/ISO3821 L/L

WELDING HOSE - OXYGEN



### APPLICATION

Delivery hose, oxygen line in welding equipments

### TUBE

Black, smooth, **SBR** rubber compound

### REINFORCEMENT

High strength synthetic plies

### COVER

Blue, smooth, **SBR/EPDM** rubber compound, abrasion and weather resistant

### WORKING TEMPERATURE

-13°F + 176°F

### SPECIFICATIONS

ISO 3821

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
6	1/4	13	1/2	0,16	20	300	60	900	50/100
8	5/16	15	19/32	0,18	20	300	60	900	50/100
9	23/64	16	5/8	0,20	20	300	60	900	50/100
10	3/8	17	21/32	0,21	20	300	60	900	50/100
13	1/2	23	29/32	0,40	20	300	60	900	50/100
19	3/4	30	1 1/16	0,62	20	300	60	900	50/100
25	1	37	1 15/32	0,86	20	300	60	900	50/100

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

### BRANDING

TGT WELBLU W.P. 20 BAR ISO 3821 ITALY